

GAMMA MODELO M (SIN SERPENTÍN)

Código	Capacidad (L) Depósito externo	Intercambio ACS Capacidad / Superficie	H	D Ø Depósito/Aislamiento
GAMM600	600	23,91 – 3,83	1644.0	700/900
GAMM800	800	27,10 – 4,34	1686.0	790/990
GAMM1000	1000	38,26 – 6,12	2041.3	790/990
GAMM1250	1250	38,26 – 6,12	2017.0	950/1150
GAMM1500	1500	46,23 – 7,40	2048.5	1000/1200
GAMM2000	2000	62,16 – 9,95	2376.9	1100/1300

GAMMA MODELO R1 CON 1 SERPENTÍN

Código	Capacidad (L) Depósito externo	Intercambio ACS Capacidad / Superficie	H	D Ø Depósito/ Aislamiento	DSUP. INT M ²
Depósito/ Aislamiento	Sup.Int m ²	175	1630	700/900	1,8
GAMR600	600	23,91 – 3,83	1644.0	700/900	2,4
GAMR800	800	27,10 – 4,34	1686.0	790/990	3,0
GAMR1000	1000	38,26 – 6,12	2041.3	790/990	3,0
GAMR1250	1250	38,26 – 6,12	2017.0	950/1150	3,6
GAMR1500	1500	46,23 – 7,40	2048.5	1000/1200	4,2
GAMR2000	2000	62,16 – 9,95	2376.9	1100/1300	4,2

GAMMA MODELO R2 CON 2 SERPENTINES

GAMR2600	600	23,91 – 3,83	1644.0	700/900	1,2/1,8
GAMR2800	800	27,10 – 4,34	1686.0	790/990	1,8/2,4
GAMR21000	1000	38,26 – 6,12	2041.3	790/990	2,4/3,0
GAMR21250	1250	38,26 – 6,12	2017.0	950/1150	2,4/3,0
GAMR21500	1500	46,23 – 7,40	2048.5	1000/1200	3,0/3,6
GAMR22000	2000	62,16 – 9,95	2376.9	1100/1300	3,6/4,2