

ACUMULADORES DE ACS INOX 444

MODELO VERTICAL DE SUELO CON 1 SERPENTÍN (VS1S)

	CAPACIDAD	100	150	200	300	400	500
	Altura [mm]		1020	1070	1320	1620	1540
Diametro [mm]		490	590	590	590	755	755
Entrada de agua fría		215	215	215	215	235	235
Resistencia eléctrica		675	675	850	1050	995	1195
Salida de agua caliente		1045	1095	1345	1645	1565	1860
Entrada serpentín		635	635	725	795	925	1065
Salida serpentín		290	290	295	295	325	325
Sonda serpentín		465	465	510	545	625	695
Las conexiones hasta 300 litros 3/4, para 400 y 500 litros de 1							

MODELO VERTICAL DE SUELO CON 2 serpentinesES (VS2S)

	CAPACIDAD	100	150	200	300	400	500
	Altura (mm)		1020	1070	1320	1620	1540
Diametro (mm)		490	590	590	590	755	755
Entrada de agua fría		215	215	215	215	235	235
Resistencia eléctrica		675	675	850	1050	995	1195
Salida de agua caliente		1045	1095	1345	1645	1565	1860
Entrada serpentín 1		635	635	725	795	925	1065
Salida serpentín 1		365	365	375	375	415	415
Sonda serpentín 1		465	465	510	545	625	695
Entrada serpentín 2		560	560	645	715	835	975
Salida serpentín 2		290	290	295	295	325	325
Sonda serpentín 2		715	715	1000	1290	1195	1445
Las conexiones hasta 300 litros 3/4, para 400 y 500 litros de 1							

MODELO VERTICAL DE SUELO CON 3 serpentinesES (VS3S)

	CAPACIDAD	200	300	400	500
	Altura (mm)		1320	1620	1540
Diametro (mm)		590	590	755	755
Entrada de agua fría		215	215	235	235
Resistencia eléctrica		850	1050	995	1195
Salida de agua caliente		1345	1645	1565	1860
Entrada serpentín 1		725	795	925	1065
Salida serpentín 1		375	375	415	415
Sonda serpentín 1		590	625	695	795
Entrada serpentín 2		645	715	835	975
Salida serpentín 2		295	295	325	325
Sonda serpentín 2		430	465	555	595
Entrada serpentín 3		1100	1290	1345	1600
Salida serpentín 3		900	1090	1045	1250
Sonda serpentín 3		1000	1190	1195	1445
Las conexiones hasta 300 litros 3/4, para 400 y 500 litros de 1					